

# Inmarsat Downconverter Narrowband Downconverter

**L-Band to 70/140 MHz**

**S-Band to 725 MHz**

**140 MHz to 15 MHz**

**Single Conversion**

Dual Channel Converters also available.



These narrowband converters of WORK Microwave are designed to meet the requirements of specific applications, where often single conversion is sufficient as the required bandwidth coverage is quite narrow and the difference of the input and output frequency is not too big. They are mainly based on the same proven core modules as used in the standard satellite upconverters and downconverters of WORK Microwave. Additional special functions can be included:

- Application specific filtering.
- Automatic level control. The output level is kept constant independent of the strength of the input signal with adjustable control characteristics.
- Additional PLO output.
- DC bias tee included at signal input to provide DC power to LNAs or LNBs.

For Inmarsat downconverters also a combination with a satellite single band downconverter, resulting in a dual channel unit, is possible.

## High signal integrity

The extreme low phase noise of the oscillators guarantees a very good signal quality. Low spurious emissions allow to use the converters also in environments with demanding requirements, like high power video uplinks. Sophisticated temperature compensation guarantees gain stability over a very wide temperature range.

## Operating and control

The converters can be operated via the push buttons on the front panel using self-explanatory display menus or via remote control (RS232, RS422/485, TCP/IP over Ethernet).

Detailed monitoring of the system status and a summary alarm output (dual change over switch contacts) are provided. For the remote control either ASCII string based commands as well as addressable, packet based commands are provided.

## Housing options

The converters normally are delivered without fans and can be operated in environments, where at minimum 1 RU space for natural ventilation is available above each unit. This eliminates the fan as potential point of failure. For rack installations without any space in between the units a fan within the converter unit is recommended, which forces an airflow from the right side to left side of the units.

# Inmarsat Downconverter

## Indoor Version

### L-Band to 70/140 MHz, Single or Dual Channel Downconverter S-Type (standard version), H-Type (extended temperature range)

<b>Downconverter Type:</b>	HCD-Lx / SCD-Lx or HCD-LxLx / SCD-LxLx	
<b>RF-Input Frequency:</b>	L-Band L1: 1525,0...1559,0 MHz (single band) L2: 1626,5...1660,5 MHz (single band) L: 1525,0...1559,0 MHz or 1626,5...1660,5 MHz (single band, input band front panel selectable) L1L1: 1525,0...1559,0 MHz and 1525,0...1559,0 MHz (dual channel) L2L2: 1626,5...1660,5 MHz and 1626,5...1660,5 MHz (dual channel) LL: 1525,0...1559,0 MHz or 1626,5...1660,5 MHz (dual channel, input band front panel selectable)	
<b>Conversion Scheme:</b>	Single down conversion, no frequency inversion	
<b>LO-Frequency:</b>	L1: 1402,0 MHz, L2: 1503,5 MHz	
<b>RF-Input Characteristics:</b>	Impedance:	50 Ω
	Return Loss:	>18 dB
	RF-Connector:	SMA female
	Max. Input Level:	-20 dBm @ IP3 < -60 dBc (operation) -10 dBm @ IP3 < -30 dBc (operation) +10 dBm (damage level)
	IIP <sub>3</sub> :	0 dBm
	Cross Talk:	Unit 1 to IF out @ unit 2: < -80 dB (only dual channel)
<b>IF-Output Characteristics:</b>	Frequency:	140 ± 17 MHz
	Impedance:	50 or 75 Ω
	Return Loss:	> 18 dB
	1 dB Compression Point:	>10 dBm, 13 dBm typical
	Output Muting:	>60 dB (by command or sense input or by alarm condition)
	IF-Signal Monitor:	-20dB of IF-output
	IF-Connector:	SMA female
<b>Transfer Characteristics:</b>	Max. Conversion Gain:	35 dB
	Attenuation Range:	0...30 dB, Step 0.1 dB (Conversion Gain 35...5 dB)
	Gain Accuracy:	± 1 dB
	Level Stability:	± 0.25 dB/day (constant temperature)
	Amplitude Response:	± 0.5 dB / 10 MHz
	Noise Figure:	<16 dB
<b>Equalizer (Gain Slope):</b>	± 2.5 dB / 40 MHz (programmable)	
<b>Intermodulation (3<sup>rd</sup> Order):</b>	-60 dBc max (Δf <sub>in</sub> : 5 MHz, P <sub>in</sub> : 2 x -40 dBm, P <sub>out</sub> : 2 x -10 dBm)	
<b>Phase Noise :</b>	10 Hz	- 55 dBc/Hz
	100 Hz	- 75 dBc/Hz
	1 kHz	- 85 dBc/Hz
	10 kHz	- 95 dBc/Hz
	100 kHz	- 100 dBc/Hz <sup>1)</sup>
	1 MHz	- 120 dBc/Hz <sup>1)</sup>
	<sup>1)</sup> 0°C to 50°C, outside this temperature range degraded by max 5 dB.	
<b>Spurious Outputs:</b>	Signal related:	< - 60 dBc (Δf < 1 MHz), < -70 dBc (Δf ≥ 1 MHz)
	Signal independent:	< - 76 dBm (< - 80 dBm typical)
<b>Frequency Stability:</b>	± 1 x 10 <sup>-7</sup> , 0°C to 50°C ± 2 x 10 <sup>-8</sup> , 0°C to 50°C (after 30 min warm up) ± 1.5 x 10 <sup>-9</sup> per day (fixed temperature after 24 h warm up)	
<b>Reference Input:</b>	Frequency:	10 MHz or 5 MHz
	Level:	-5...10 dBm
	Modes:	internal, external, auto (senses reference input)
	Connector:	SMA female
<b>Reference Output:</b>	Frequency:	10 MHz
	Impedance:	50 Ω
	Return Loss:	>15 dB
	Level:	0 ± 3 dBm
	Connector:	SMA female
<b>Reference Output: with Option: -PLO</b>	Frequency:	187.20 MHz (other frequencies on request)
	Impedance:	50 Ω
	Return Loss:	> 15 dB
	Harmonics:	< -40 dBc
	Level:	11 ± 1.5 dBm
	Connector:	SMA female
<b>Monitoring and Control Interface:</b>	RS232 or RS422/RS485 (Connectors DSUB09 female) (selectable by customer), TCP/IP over Ethernet, 10/100 Base-T (RJ45 connector)	
<b>Alarm Interface: Mute Input:</b>	Two potential free contacts (DPDT) Mute Input: TTL logic input with internal pull up Connector DSUB09 female)	
<b>Temperature Range:</b>	HCU : -30°C to 60°C operating (10 minutes warm up at -30°C, the LCD display is operational: -20°C to 60°C) SCU : 0°C to 50°C operating - 30°C to 80°C storage	
<b>Relative Humidity:</b>	< 95 % non condensing	
<b>User Interface:</b>	SCU: LCD-Display 2 x 40 characters, 4 cursor keys, 4 function keys HCU: VFD-Display 2 x 40 characters, 4 cursor keys, 4 function keys	

Specifications continued next page

# Inmarsat Downconverter

## Indoor Version

### L-Band to 70/140 MHz Downconverter S-Type (standard version), H-Type (extended temperature range)

Specifications continued:

<b>Power Supply:</b>	85...264 V AC, 40...70 Hz, 0.9 A max
<b>DC Power to external LNA: with Option DC (DC bias tee included at Signal input)</b>	DC Voltage : 15 V (other voltages on request) Current : max. 0.4 A (each output) Switchable: ON / OFF Protection: Short circuit protection
<b>Dimension and Weight:</b>	483 x 44 x 500 mm <sup>3</sup> , 1 RU (19") appr. 8.6 kg

Specifications are subject to change

Order Information:

**HCD-[RF Band(s)]-[IF Band in MHz]-[IF Imp in Ω]-[Options]**

**SCD-[RF Band(s)]-[IF Band in MHz]-[IF Imp in Ω]-[Options]**

**Possible Options are:**

**FAN** (internal Fan)

**VFD** (VFD display, standard with HCD-type converters)

**DC15** (DC bias tee on signal input with 15 V DC output)

**PLO187** (additional 187 MHz reference signal output)

**ALC-BW** (Automatic level control- Filter bandwidth, see product:  
Automatic Level Control)

**Examples:**

**HCD-L1-140-50**

**SCD-L2L2-140-75-FAN-DC15-PLO187**

**HCD-LL-140-50-FAN-DC15**

**SCD-LC-140-50-FAN**

Combination with of L-Band (Narrowband) Downconverter and  
C-Band Satellite Downconverter) with Fan

# Satellite Narrowband Downconverter

## Indoor Version

### S-Band to 725 MHz Downconverter

### S-Type (standard version), H-Type (extended temperature range)

<b>Downconverter Type:</b>	SCD-S	
<b>Frequency resolution:</b>	100 kHz	
<b>RF-Input Frequency:</b>	2.3...2.95 GHz	
<b>Conversion Scheme:</b>	Single down-conversion, no frequency inversion	
<b>LO Frequency:</b>	1.55...2.25 GHz	
<b>RF-Input Characteristics:</b>	Impedance:	50 Ω
	Return Loss:	> 15 dB (VSWR = 1.22)
	Maximum Aggregate Input Level:	0 dBm
	LO Leakage	-42 dBm max.
	RF-Connector	SMA female
<b>IF-Output Characteristics:</b>	Frequency:	700...750 MHz
	Impedance:	50 Ω
	Return Loss:	> 15 dB (VSWR = 1.22)
	1 dB Compression Point:	> +7 dBm
	IF-Connectors:	SMA female
<b>Transfer Characteristics:</b>	Conversion Gain:	5...35 dB
	Gain-Resolution:	1 dB
	Gain Accuracy:	± 0.2 dB typical (± 0.3 dB max.)
	Gain Stability:	± 0.25 dB/day (constant temperature)
	Amplitude Ripple:	± 0.2 dB / 20 MHz
	IF Output Bandwidth (3 dB):	1 GHz <sup>2)</sup> / 20 MHz
	Noise Figure:	< 12 dB <sup>2)</sup>
<b>Group Delay (700...750 MHz):</b>	Flat, Ripple:	1 ns peak to peak max.
<b>Intermodulation (3<sup>rd</sup> Order):</b>	-60 dBc max ( $\Delta f_{in}$ : 5 MHz, $P_{out\ ges}$ : < -12 Bm) (OIP3 = +15 dBm)	
<b>AM / PM conversion:</b>	0.1° / dB ( $P_{out}$ = 0 dBm)	
<b>Phase Noise:</b>	10 Hz	- 50 dBc/Hz
	100 Hz	- 70 dBc/Hz
	1 kHz	- 80 dBc/Hz
	10 kHz	- 83 dBc/Hz
	100 kHz	- 95 dBc/Hz <sup>1)</sup>
	1 MHz	- 111 dBc/Hz <sup>1)</sup>
	1) 0°C to 50°C, outside this temperature range degraded by max 5 dB.	
<b>Spurious Outputs:</b>	Signal dependent:	< - 55 dBc
<b>Frequency Stability:</b>	± 1 x 10 <sup>-7</sup> , 0°C to 50°C with OCXO ± 2 x 10 <sup>-8</sup> , 0°C to 50°C (after 10 min warm up) ± 1.5 x 10 <sup>-8</sup> per day (fixed temperature after 24 h warm up)	
<b>Test Output: (Microwave Oscillator)</b>	not available	
<b>Temperature Range:</b>	0 °C to 50 °C operating - 30 °C to 80 °C storage	
<b>Relative Humidity:</b>	< 95 % non condensing	
<b>Power Supply:</b>	85...264 V AC, 40...70 Hz	
<b>Power Consumption:</b>	Max: 24 VA / 14 W Typ: 20 VA / 11 W	
<b>User Interface</b>	LCD, 2 x 40 characters, 4 cursor keys, 2 function keys Mains Power Switch on Front Panel	
<b>Mains Fuse:</b>	3.15 A time-lag fuse	
<b>Dimension and Weight:</b>	483 x 44 x 323 mm <sup>3</sup> , 1 RU (19") (maximum Dimension) 436 x 44 x 280 mm <sup>3</sup> (Dimension without Front panel) appr. 3.5 kg	

Specifications are subject to change

**Order Information:** SCD-S-725 [IF Band in MHz]-LC

**Examples:**

SCD-S-725-50-LC

SCD-S-725-75-LC

# Satellite Downconverter Narrowband

## Indoor Version

### 140 MHz to 15 MHz Downconverter

### S-Type (standard version), H-Type (extended temperature range)

<b>Downconverter Type:</b>	DNC-V		
<b>VHF-Input Frequency:</b>	80...200 MHz		
<b>Conversion Scheme:</b>	Single down-conversion, no frequency inversion		
<b>LO Frequency:</b>	80...200 MHz, Resolution 10 Hz		
<b>RF-Input Characteristics:</b>	Impedance:	50 $\Omega$	
	Return Loss:	> 14 dB	
	Maximum Aggregate Input Level:	approx. -25 dBm (operational) approx. +10 dBm (damage level)	
	RF-Connector:	BNC female	
<b>IF-Output Characteristics:</b>	Frequency:	0...30 MHz	
	Impedance:	50 $\Omega$	
	Return Loss:	> 20 dB	
	1 dB Compression Point:	> 10 dBm	
	Output Muting:	> 60 dB (during warm-up or during alarm condition)	
	IF-Connectors:	BNC female	
<b>Transfer Characteristics:</b>	Conversion Gain:	45 dB	
	Attenuation Range:	0...30 dB, Step 0.1 dB (Conversion Gain 45...15 dB)	
	Gain Accuracy:	$\pm 1.5$ dB	
	Level Stability:	$\pm 0.25$ dB/day (constant temperature)	
	Amplitude Ripple:	$\pm 0.25$ dB / 20 MHz	
	Noise Figure:	< 20 dB	
<b>Internal Filter*:</b>	4 internal filters		
	80...110 MHz		
	110...140 MHz		
	140...170 MHz		
	170...200 MHz		
*) other filter characteristics on request			
<b>External Filter:</b>	via BNC connectors Impedance: 50 Ohms		
<b>Phase Noise:</b>	10 Hz	- 80 dBc/Hz	1) 0°C to 50°C, outside this temperature range degraded by max 5 dB.
	100 Hz	- 100 dBc/Hz	
	1 kHz	- 110 dBc/Hz	
	10 kHz	- 120 dBc/Hz	
	100 kHz	- 125 dBc/Hz <sup>1)</sup>	
<b>Spurious Outputs:</b>	< - 70 dB		
<b>Frequency Stability:</b>	$\pm 1 \times 10^{-7}$ , 0°C to 50°C $\pm 2 \times 10^{-8}$ , 0°C to 50°C (after 10 min warm up) $\pm 1.5 \times 10^{-9}$ per day (fixed temperature after 24 h warm up)		
<b>Reference Input:</b>	Frequency:	10 MHz or 5 MHz	
	Level:	-3...10 dBm	
	Modes:	internal, external, auto (senses reference input)	
	Impedance:	50 $\Omega$	
	Connector:	BNC female	
<b>Reference Output:</b>	Frequency:	10 MHz	
	Level:	0 $\pm$ 3 dBm	
	Impedance:	50 $\Omega$	
	Connector:	BNC female	
<b>Monitoring and Control Interface:</b>	TCP/IP over Ethernet (10 or 100 Mbit/s, auto sensing) RS232 or RS422/RS485 (Connectors DSUB09 female) (configurable by software) Mute Input: TTL logic input with internal pull up		
<b>Temperature Range:</b>	0°C to 50°C operating - 30°C to 80°C storage		
<b>Relative Humidity:</b>	< 95 % non condensing		
<b>User Interface:</b>	LCD-Display 2 x 40 characters, 4 cursor keys, 2 function keys		
<b>Power Supply:</b>	85...264 V AC, 40...70 Hz		
<b>Power Consumption:</b>	Max: 33 VA / 20 W Typ: 29 VA / 18 W		
<b>Mains Fuse:</b>	2 x 3.15 A time-lag fuse		
<b>Dimension and Weight:</b>	483 x 44 x 260 mm <sup>3</sup> , 1 RU (19") approx. 4.2 kg		

Specifications are subject to change

Order Information: **DNC-V-15-50**