

VF-4210A

Rubidium Standard Frequency References



Features

- 10MHz rubidium frequency reference
- 100kHz capability (with multiple RF output options)
- 1 PPS disciplining input (standard)
- Ultra low phase noise (-130 dBc at 10Hz)
- RS-232-C monitor/control
- Convenient 2U bench or 19" rack mount

Applications

- Laboratory
- Systems Frequency Reference



Description

The VF-4210A Rubidium Standard Frequency Reference is a unique solution for providing a highly stable, low phase noise, frequency reference for applications requiring atomic reference stability performance.

The instrument contains a high performance rubidium module, with an extended life design, and very low aging rate to deliver excellent stability. The module is the reference for a high quality OCXO output for low phase noise and jitter.

For even better long term stability the unit will accept a 1 PPS input that can be derived from a reference source such as cesium clock or GPS module.

The VF-4210A is an ideal laboratory or system frequency reference with a range of options to enhance the functionality of the unit.

VF-4210A

Rubidium Standard

Frequency References



Electrical Specifications

Parameter	Condition	Value	Note
Output Level	Standard 10MHz 1 PPS	0.5V RMS into 50 Ohms 5V CMOS ± 20 mA sink/source	
	Multiple Outputs Option 1MHz 5MHz 10MHz 1 PPS	1.0V RMS into 50 Ohms +13 dBm ± 1 dBm 1.0V RMS into 50 Ohms +13 dBm ± 1 dBm 1.0V RMS into 50 Ohms +13 dBm ± 1 dBm 4.2V CMOS into 50 Ohms	
Accuracy		5E-11 (at shipment)	
Spurious		-130 dBc (100kHz BW)	
Aging		<5 E-11/month (after 30 days) <5 E-10/year	
Stability	1s 10s 100s	2E-11 1E-11 2E-12	Short-term
Phase Noise (1Hz BW)	10Hz 100Hz	-130 -140	
Front Panel Display	Indicators Power Lock Fault	Green LED Green LED Amber LED	

Environmental and Physical

Parameter	Specification
Operating Temperature	0°C to +50°C
Storage Temperature	-20°C to +70°C
Relative Humidity	0-95%, non-condensing
Power Requirements	AC Input Voltage: 90-264V, <10W DC Input (optional): 18-72V
Weight	Unit: <15 lbs.

VF-4210A

Rubidium Standard Frequency References



Rear View

VF-4210A w/MOPS option



2U (3.504 inches) x 19 inches x 12 inches

How to order:

VF-4210A

Available Options

Option	Description
VF-MOPS	Multiple RF outputs (1MHz, 5MHz, 10MHz)
VF-EXP4	4 channel expansion module
VF-RF01	1MHz sine wave out (x4)
VF-RF05	5MHz sine wave out (x4)
VF-RF10	10MHz sine wave out (x4)
VF-PULS	Pulse distribution (x4)
VF-OCXO	High performance OCXO
VF-ULNO	Ultra low noise output
VF-DCPS	DC power supply
VF-RSLD	Mounted rack slides